





PRODUCT NUMBER: 840-13-002-00-011000

www.mill-max.com
DATA SHEET



General Info	
1 Description:	Solder Cup Strip Socket Accepts .022"-.042" (0,559-1,067mm) dia leads
Type:	Interconnect
Category:	Machined Pin Socket
Mounting Style:	Mounting Tabs with 4-40 Threaded Inserts
# Pins:	2
2 Packaging:	Packaged in Box or Tube
Rows:	Single Row
ECCN:	Contact Factory
HTSUS:	8536.90.4040
Product Lifecycle:	Active
Country Of Origin:	USA

840-13-002-00-011000- SPECIFICATIONS

Environmental Specs	
3	Temperature Range: -55/+125° C
4	Shock: No Elect. Discontinuity > 1µs @ 50g
5	Vibration: No Elect. Discontinuity > 1µs @ 10-2000HZ, 15 G
6	RoHS: Yes
Moisture Sensitivity Level (MSL): 1 (Unlimited)	
REACH Status: REACH Unaffected	
Materials	
Loose Pin/Receptacle #(Material): 3042 (Brass Alloy)	
Shell Plating: 10 µ" Gold over 100 µ" Nickel	
Inner Contact #: 36	
# Contact Fingers: 4	
Inner Contact Material: Beryllium Copper	
Inner Contact Plating: 30 µ" Gold over 50 µ" Nickel	
Insulator Material: Nylon 4/6	
Technical Specs	
Pitch: .158" (4,001mm)	
Electrical Specs	
Rated Voltage: 100 VRMS/150 VDC	
Insulation Resistance: 10,000 MΩ min.	
Dielectric Withstanding Voltage: 1,000 VRMS min.	

NOTES:

1. Standard Tolerances

Assembly tolerance: +/- .010" (.25mm)

Connector Length "L"

Connector Length "L"	Tolerance
L ≤ 2" (L ≤ 50.8 mm)	+/- .005" (+/- .127 mm)
2< L ≤ 3" (50.8 < L ≤ 76.2 mm)	+ .007 / - .006" (+ .178 / - .152 mm)
3< L ≤ 4" (76.2 < L ≤ 101.6 mm)	+ .009 / - .007" (+ .229 / - .178 mm)
4< L ≤ 5" (101.6 < L ≤ 127 mm)	+ .011 / - .008" (+ .279 / - .203 mm)
5< L ≤ 6.4" (127 < L ≤ 162.56 mm)	+ .013 / - .009" (+ .330 / - .229 mm)

Insulator width: +/- .005 (.13mm)

Insulator height: +/- .005 (.13mm)

Co-planarity of SMT connectors: .005" (.13mm) up to 1" (25.4mm) in connector length

Insulator Flatness: .005" (.13mm) up to 1" (25.4mm) in connector length

Pin Length: +/- .005 (.13mm)

Pin Diameter: +/- .002 (.051mm)

Pin Angle: +/- 2°

2. Not all part numbers in the series may be packaged in tubes. Some specific part numbers may be packaged in a box.
3. Per IEC 60512-11-(4,-9,-10,-12)
4. For discrete pin only. Per IEC 60512-6-3: Test 6c: Shock
5. For discrete pin only. Per IEC 60512-6-4: Test 6d: Vibration (sinusoidal)
6. Mill-Max products labeled with the RoHS symbol are compliant with all three ROHS Directives. All of our products previously described as RoHS (2002/95/EC) and RoHS-2 (2011/65/EC) are also compliant with RoHS-3 (2015/863/EU).

ADDITIONAL NOTES AND SPECIFICATIONS

In the interest of improved design, quality and performance , Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

RELATED LINKS AND DOCUMENTS

- Product Detail: [840-13-002-00-011000 - Solder Cup Strip Socket](#)
- Environmental Compliance: <https://www.mill-max.com/rohs>