

TECHNICAL DATA SHEET

Part No. 157-00151
Article No. 157-00151
Type T50SOSSB5-High-E-C-CC



Oval Shaped Stud Mount's special design allows for a 0.2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.

Material	Polyamide 6.6 heat stabilized (PA66HS)
Operating Temperature	-40°F to +257°F (-40°C to +125°C)
Flammability	UL 94 V-2
UV Resistant	No
Use Conditions	For Indoor Use Only
Color	Gray (GY)
Pkg. Qty.	1000
Carton Qty.	3000
Customs Number	3926909988

Fixation Method	Stud Mount
Length (imperial)	6.57 "
Length (metric)	167.0 mm
Max. Bundle Diameter (imperial)	1.38 "
Max. Bundle Diameter (metric)	35.0 mm
Min. Tensile Strength (imperial)	50 lbs
Min. Tensile Strength (metric)	222.4 N
Stud Diameter (imperial)	0.20 "
Stud Diameter (metric)	5.0 mm, 6.0 mm
Width (imperial)	0.20 "
Width (metric)	5.0 mm

