


RV-8263-C7

Real-Time Clock Module with I²C-Bus




DIMENSIONS

Package:



Recommended Solder Pad:



Metal lid is connected to V_{SS} (pin #2)

All dimensions in mm typical

APPLICATIONS

IoT
Metering
Industrial
Automotive
Health Care
Wearables, Portables


DESCRIPTION

The RV-8263-C7 is an SMD Real-Time Clock Module that incorporates an integrated CMOS circuit together with an XTAL. It operates under vacuum in a hermetically sealed ceramic package with metal lid.

FEATURES

- Low power consumption: 190 nA @ 3 V.
- Wide operating voltage range: 0.9 V to 5.5 V.
- Time accuracy: ±20 ppm @ 25°C.
- Operating temperature range: -40 to +85°C.
- User programmable offset value.
- Oscillator stop detection.
- Provides year, month, date, weekday, hours, minutes and seconds.
- Automatic leap year calculation: 2000 to 2099.
- Timer and Alarm functions.
- Clock output frequencies: 32.768 kHz to 1 Hz.
- I²C-bus interface: 400 kHz.
- 100% Pb-free, RoHS-compliant.
- Automotive qualification according to AEC-Q200 available.

BLOCK DIAGRAM



ELECTRICAL CHARACTERISTICS AT 25°C

More detailed information can be found in the Application Manual.

	Symbol	Condition	Min.	Typ.	Max	Unit
Supply voltage	V_{DD}	I ² C-bus active	1.8		5.5	V
Supply voltage	V_{DD}	Time keeping	0.9		5.5	V
Current consumption Time keeping mode	I_{DDO}	I ² C-bus inactive, $V_{DD} = 3\text{ V}$		190	240	nA
CLKOUT frequency	F_{CLKOUT}	Programmable	32768 to 1			Hz
Frequency tolerance	$\Delta F/F$	@ 25°C	± 20 ¹⁾			ppm
Aging first year max.	$\Delta F/F$	@ 25°C	± 3			ppm

1) Tighter frequency tolerances on request.


ENVIRONMENTAL CHARACTERISTICS

		Conditions	Max. Dev.
Storage temperature range		-55 to +125°C	
TA Operating temperature range		-40 to +85°C	
Shock resistance	$\Delta F/F$	5000 g, 0.3 ms, 1/2 sine	± 5 ppm
Vibration resistance	$\Delta F/F$	20 g / 10–2000 Hz	± 5 ppm

TERMINATIONS AND PROCESSING

Package	Termination	Processing
SON-8	Au flashed pads	IPC/JEDEC J-STD-020C 260°C / 20 - 40 s

FREQUENCY TEMPERATURE CHARACTERISTICS



PIN CONNECTIONS TOP VIEW

		Pin	Connection
Product Date Code #8 #5 M637A1 8263 #1 #4 Part Designation Pin 1 Index		1	NC Not connected
		2	V_{SS} Ground
		3	CLKOE Clock Output Enable
		4	$\overline{\text{INT}}$ Interrupt Output
		5	V_{DD} Power Supply Voltage
		6	CLKOUT Clock Output
		7	SCL Serial Clock Input
		8	SDA Serial Data

ORDERING INFORMATION

RV - 8263 - C7 TA QC		
RTC module		Qualification
Product type		QC = Commercial Grade (Standard)
		QA = Automotive Grade AEC-Q200
Package size		Temperature range
C7 = 3.2 x 1.5 x 0.80 mm		TA = -40 to +85°C (Standard)
A unique part number will be generated for each product specification, i.e:		
20xxxx-MG01	1'000 pcs (in 12 mm tape on 7" reel)	
20xxxx-MG03	3'000 pcs (in 12 mm tape on 7" reel)	

All specifications subject to change without notice.



A COMPANY OF THE SWATCH GROUP

Micro Crystal AG
Muehlestrasse 14
CH-2540 Grenchen
Switzerland

Phone +41 32 655 82 82
sales@microcrystal.com
www.microcrystal.com