

# Subminiature Plastic Silicon Infrared Phototransistor

## QSB363

### Description

The QSB363 is a silicon phototransistor encapsulated in a black infrared transparent T-3/4 package.

### Features

- NPN Silicon Phototransistor
- T-3/4 (2 mm) Surface Mount Package
- Medium Wide Beam Angle: 24°
- Black Plastic Package
- Matched Emitters: QEB363 or QEB373
- Daylight Filter
- Lead Form Options: Gullwing, Yoke, Z-Bend
- This is a Pb-Free Device and Halide Free Device



**ABSOLUTE MAXIMUM RATINGS** (Values are at TA = 25°C unless specified otherwise).

| Symbol             | Parameter                                    | Value      | Unit |
|--------------------|----------------------------------------------|------------|------|
| T <sub>OPR</sub>   | Operating Temperature                        | -40 to +85 | °C   |
| T <sub>STG</sub>   | Storage Temperature                          | -40 to +85 | °C   |
| T <sub>SOL-I</sub> | Soldering Temperature (Iron)<br>(Notes 1, 2) | 260        | °C   |
| T <sub>SOL-F</sub> | Soldering Temperature (Flow)<br>(Notes 1, 2) | 260        | °C   |
| V <sub>CEO</sub>   | Collector-Emitter Voltage                    | 30         | V    |
| V <sub>ECO</sub>   | Emitter-Collector Voltage                    | 5          | V    |
| P <sub>C</sub>     | Power Dissipation (Note 3)                   | 75         | mW   |


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. RMA flux is recommended.
2. Methanol or isopropyl alcohols are recommended as cleaning agents.
3. Derate power dissipation linearly 1.08 mW/°C above 25°C.


### SCHEMATIC




T-3/4 2.50 x 2.00  
CASES 100CB



T-3/4 2.50 x 2.00  
CASES 100EH



T-3/4 2.50 x 2.00  
CASES 100EJ



T-3/4 2.50 x 2.00  
CASES 100EK

### ORDERING INFORMATION

| Device   | Package                                           | Shipping†             |
|----------|---------------------------------------------------|-----------------------|
| QSB363   | T-3/4 2.50 x 2.00 100CB<br>(Pb-Free, Halide Free) | 1000 /<br>Bulk Bag    |
| QSB363GR | T-3/4 2.50 x 2.00 100EH<br>(Pb-Free, Halide Free) | 1000 /<br>Tape & Reel |
| QSB363YR | T-3/4 2.50 x 2.00 100EJ<br>(Pb-Free, Halide Free) | 1000 /<br>Tape & Reel |
| QSB363ZR | T-3/4 2.50 x 2.00 100EK<br>(Pb-Free, Halide Free) | 1000 /<br>Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, [BRD8011/D](#).

## QSB363

### ELECTRICAL/OPTICAL CHARACTERISTICS (Values are at $T_A = 25^\circ\text{C}$ unless specified otherwise).

| Symbol        | Parameter                            | Test Conditions                                                                      | Min | Typ      | Max | Unit          |
|---------------|--------------------------------------|--------------------------------------------------------------------------------------|-----|----------|-----|---------------|
| $\lambda_P$   | Peak Sensitivity Wavelength          |                                                                                      | –   | 940      | –   | nm            |
| $\Theta$      | Reception Angle                      |                                                                                      | –   | $\pm 12$ |     | °             |
| $I_{CEO}$     | Collector Dark Current               | $V_{CE} = 20\text{ V}$ , $E_e = 0\text{ mW/cm}^2$                                    | –   | –        | 100 | nA            |
| $BV_{CEO}$    | Collector–Emitter Breakdown Voltage  | $I_C = 100\text{ }\mu\text{A}$ , $E_e = 0\text{ mW/cm}^2$                            | 30  | –        | –   | V             |
| $BV_{ECO}$    | Emitter–Collector Breakdown Voltage  | $I_E = 100\text{ }\mu\text{A}$ , $E_e = 0\text{ mW/cm}^2$                            | 5   | –        | –   | V             |
| $I_{C(ON)}$   | On–State Collector Current           | $V_{CE} = 5\text{ V}$ , $E_e = 1\text{ mW/cm}^2$ ,<br>$\lambda = 940\text{ nm GaAs}$ | 1.0 | 1.5      | –   | mA            |
| $V_{CE(SAT)}$ | Collector–Emitter Saturation Voltage | $I_C = 2\text{ mA}$ , $E_e = 1\text{ mW/cm}^2$ ,<br>$\lambda = 940\text{ nm GaAs}$   | –   | –        | 0.4 | V             |
| $t_r$         | Rise Time                            | $V_{CE} = 5\text{ V}$ , $I_C = 1\text{ mA}$ , $R_L = 1000\text{ }\Omega$             | –   | 15       | –   | $\mu\text{s}$ |
| $t_f$         | Fall Time                            |                                                                                      | –   | 15       | –   | $\mu\text{s}$ |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. Collector Power Dissipation vs. Ambient Temperature




Figure 2. Spectral Sensitivity




Figure 3. Relative Collector Current vs. Ambient Temperature




Figure 4. Collector Current vs. Irradiance




Figure 5. Collector Dark Current vs. Ambient Temperature





Figure 6. Collector Current vs. Collector Emitter Voltage





**T-3/4 2.50x2.00**  
**CASE 100CB**  
**ISSUE A**

DATE 14 SEP 2023

**NOTES:**


1. CONTROLLING DIMENSIONS: MILLIMETERS
2. DIMENSIONS DO NOT INCLUDE MOLD FLASH OR BURRS.
3. 2MM DETECTOR



| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | 2.50        | 2.70 | 2.90 |
| A2  | 1.30        | 1.40 | 1.50 |
| A3  | 1.30        | 1.40 | 1.50 |
| A4  | 0.60 REF    |      |      |
| b   | 0.45        | 0.55 | 0.65 |
| b1  | 0.35        | 0.45 | 0.55 |
| c   | 0.10        | 0.15 | 0.25 |
| D   | 2.30        | 2.50 | 2.70 |
| E   | 1.80        | 2.00 | 2.20 |
| L   | 7.00        | ---  | ---  |
| øD  | 1.70        | 1.90 | 2.10 |

|                         |                        |                                                                                                                                                                                     |
|-------------------------|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON13435G</b>     | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>T-3/4 2.50x2.00</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |



onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.


**T-3/4 2.50x2.00**  
**CASE 100EH**  
**ISSUE O**


DATE 14 SEP 2023

## NOTES:

1. CONTROLLING DIMENSIONS: MILLIMETERS
2. DIMENSIONS DO NOT INCLUDE MOLD FLASH OR BURRS.
3. 2MM GULLWING DETECTOR.



| DIM | MILLIMETERS |       |       |
|-----|-------------|-------|-------|
|     | MIN.        | NOM.  | MAX.  |
| A   | 2.500       | 2.700 | 2.900 |
| A2  | 1.300       | 1.400 | 1.500 |
| A3  | 1.200       | 1.300 | 1.400 |
| A4  | 0.750       | 0.850 | 0.950 |
| A5  | 0.650       | 0.750 | 0.850 |
| A6  | 0.550       | 0.650 | 0.750 |
| b   | 0.450       | 0.550 | 0.650 |
| b1  | 0.350       | 0.450 | 0.550 |
| c   | 0.100       | 0.150 | 0.200 |
| D   | 2.300       | 2.500 | 2.700 |
| D1  | 1.200       | 1.400 | 1.600 |
| D2  | 0.900       | 1.100 | 1.300 |
| E   | 1.800       | 2.000 | 2.200 |
| H   | 3.800       | 4.000 | 4.200 |
| L   | 0.200       | 0.300 | 0.400 |
| ØD  | 1.700       | 1.900 | 2.100 |
| R1  | 0.700       | 0.800 | 0.900 |




## RECOMMENDED MOUNTING FOOTPRINT\*

\*FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

|                         |                        |                                                                                                                                                                                     |
|-------------------------|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON57119H</b>     | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>T-3/4 2.50x2.00</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.




**T-3/4 2.50x2.00**  
**CASE 100EJ**  
**ISSUE O**


DATE 14 SEP 2023

**NOTES:**

1. CONTROLLING DIMENSIONS: MILLIMETERS
2. DIMENSIONS DO NOT INCLUDE MOLD FLASH OR BURRS.
3. 2MM YOKE DETECTOR.




**TOP VIEW**



**BOTTOM VIEW**

| DIM | MILLIMETERS |       |       |
|-----|-------------|-------|-------|
|     | MIN.        | NOM.  | MAX.  |
| A   | 2.500       | 2.700 | 2.900 |
| A2  | 1.300       | 1.400 | 1.500 |
| A3  | 1.200       | 1.300 | 1.400 |
| A4  | 0.650       | 0.750 | 0.850 |
| A5  | 0.550       | 0.650 | 0.750 |
| b   | 0.450       | 0.550 | 0.650 |
| b1  | 0.350       | 0.450 | 0.550 |
| c   | 0.100       | 0.150 | 0.200 |
| D   | 2.300       | 2.500 | 2.700 |
| D1  | 1.200       | 1.400 | 1.600 |
| D2  | 0.900       | 1.100 | 1.300 |
| E   | 1.800       | 2.000 | 2.200 |
| H   | 7.200       | 7.400 | 7.600 |
| H1  | 4.500       | 4.700 | 4.900 |
| ØD  | 1.700       | 1.900 | 2.100 |
| R1  | 0.700       | 0.800 | 0.900 |
| R2  | 0.300       | 0.400 | 0.500 |




**RECOMMENDED MOUNTING FOOTPRINT\***

\*FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDDRM/D.

|                         |                        |                                                                                                                                                                                     |
|-------------------------|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON57120H</b>     | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>T-3/4 2.50x2.00</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.





**T-3/4 2.50x2.00**  
**CASE 100EK**  
**ISSUE O**


DATE 14 SEP 2023

NOTES:

1. CONTROLLING DIMENSIONS: MILLIMETERS
2. DIMENSIONS DO NOT INCLUDE MOLD FLASH OR BURRS.
3. 2MM ZBEND DETECTOR.



| DIM      | MILLIMETERS |       |       |
|----------|-------------|-------|-------|
|          | MIN.        | NOM.  | MAX.  |
| A        | 2.500       | 2.700 | 2.900 |
| A2       | 1.300       | 1.400 | 1.500 |
| A3       | 1.200       | 1.300 | 1.400 |
| A4       | 0.550       | 0.650 | 0.750 |
| A5       | 0.650       | 0.750 | 0.850 |
| b        | 0.450       | 0.550 | 0.650 |
| b1       | 0.350       | 0.450 | 0.550 |
| c        | 0.100       | 0.150 | 0.200 |
| D        | 2.300       | 2.500 | 2.700 |
| D1       | 1.200       | 1.400 | 1.600 |
| D2       | 0.900       | 1.100 | 1.300 |
| E        | 1.800       | 2.000 | 2.200 |
| H        | 5.600       | 5.800 | 6.000 |
| H1       | 4.100       | 4.300 | 4.500 |
| H2       | 2.850       | 3.050 | 3.250 |
| $\phi D$ | 1.700       | 1.900 | 2.100 |
| R1       | 0.700       | 0.800 | 0.900 |



RECOMMENDED MOUNTING FOOTPRINT\*

\*FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERM/D.

|                  |                 |                                                                                                                                                                                     |
|------------------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98AON57121H     | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | T-3/4 2.50x2.00 | PAGE 1 OF 1                                                                                                                                                                         |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)