

# TPS65262-1 具有双路可调 350mA/150mA 低压降稳压器 (LDO) 的 4.5V 至 18V 输入电压, 3A/1A/1A 输出电流三路同步降压转换器

## 1 特性

- 工作输入电压范围：4.5V 至 18V
- 反馈基准电压：0.6V  $\pm$ 1%
- 最大连续输出电流：3A/1A/1A
- 600kHz 固定开关频率
- 集成双路 LDO：
  - 输入电压范围：1.3V 至 5.5V
  - 持续输出电流：350mA/150mA
- 针对 Buck1 的可编程软启动时间
- 针对 Buck2 和 Buck3 的固定软启动时间 1ms
- 针对 Buck2 和 Buck3 的内部环路补偿
- 针对每个降压转换器的专用使能引脚
- 自动加电和断电序列
- 轻负载条件下的脉冲跳跃模式 (PSM)
- 输出电压电源正常状态指示器
- 热过载保护

## 2 应用

- 数字电视 (DTV)
- 机顶盒
- 家庭网关和接入点网络
- 无线路由器
- 安全监控
- POS 机

## 3 说明

TPS65262-1 是一款具有 3A/1A/1A 输出电流的单片三路同步降压 (降压) 转换器。4.5V 至 18V 的宽输入电源电压范围包括大多数运行自 5V、9V、12V 或 15V 电源总线的中间总线电压。该转换器具有恒定频率峰值电流模式, 专用于简化应用, 同时方便设计人员根据目标应用来优化系统。此器件运行在 600kHz 的固定开关频率上。为了减少外部组件数量, 已经集成针对 buck2 和 buck3 的环路补偿。buck1 和 buck2, buck3 之间的 180° 异相运行 (buck2 和 buck3 同相运行) 可最大限度降低对输入滤波器的要求。轻载条件下, 该器件自动在脉冲跳跃模式 (PSM) 下运行, 从而通过减少开关损耗来提供高效率。

TPS65262-1 内置两个低压降线性稳压器 (LDO), 它们的输入电压范围为 1.3V 至 5.5V, 持续输出电流为 350/150mA, 具有独立使能和可调输出电压特性。


TPS65262-1 特有自动电源序列, 可将 MODE 引脚驱动为高电平, 并配置 EN1、EN2 和 EN3 引脚。

该器件具有过压保护、过流保护、短路保护和过热保护功能。电源正常引脚在任何降压输出电压降至稳压范围之外时被置为有效。


### 封装信息<sup>(1)</sup>

| 器件型号       | 封装             | 封装尺寸 (标称值)             |
|------------|----------------|------------------------|
| TPS65262-1 | RHB (VQFN, 32) | 5.00mm $\times$ 5.00mm |

(1) 要了解所有可用封装, 请见数据表末尾的可订购产品附录。



典型应用



效率与输出负载之间的关系



## Table of Contents

|                                                |           |                                                                  |           |
|------------------------------------------------|-----------|------------------------------------------------------------------|-----------|
| <b>1 特性</b> .....                              | <b>1</b>  | 8.3 Feature Description.....                                     | <b>16</b> |
| <b>2 应用</b> .....                              | <b>1</b>  | 8.4 Device Functional Modes.....                                 | <b>23</b> |
| <b>3 说明</b> .....                              | <b>1</b>  | <b>9 Application and Implementation</b> .....                    | <b>25</b> |
| <b>4 Revision History</b> .....                | <b>2</b>  | 9.1 Application Information.....                                 | <b>25</b> |
| <b>5 Device Comparison Table</b> .....         | <b>3</b>  | 9.2 Typical Application.....                                     | <b>25</b> |
| <b>6 Pin Configuration and Functions</b> ..... | <b>4</b>  | 9.3 Power Supply Recommendations.....                            | <b>35</b> |
| <b>7 Specifications</b> .....                  | <b>6</b>  | 9.4 Layout.....                                                  | <b>35</b> |
| 7.1 Absolute Maximum Ratings.....              | <b>6</b>  | <b>10 Device and Documentation Support</b> .....                 | <b>37</b> |
| 7.2 ESD Ratings.....                           | <b>6</b>  | 10.1 接收文档更新通知.....                                               | <b>37</b> |
| 7.3 Recommended Operating Conditions.....      | <b>6</b>  | 10.2 支持资源.....                                                   | <b>37</b> |
| 7.4 Thermal Information.....                   | <b>7</b>  | 10.3 Trademarks.....                                             | <b>37</b> |
| 7.5 Electrical Characteristics.....            | <b>8</b>  | 10.4 静电放电警告.....                                                 | <b>37</b> |
| 7.6 Typical Characteristics.....               | <b>11</b> | 10.5 术语表.....                                                    | <b>37</b> |
| <b>8 Detailed Description</b> .....            | <b>15</b> | <b>11 Mechanical, Packaging, and Orderable Information</b> ..... | <b>37</b> |
| 8.1 Overview.....                              | <b>15</b> |                                                                  |           |
| 8.2 Functional Block Diagram.....              | <b>16</b> |                                                                  |           |

## 4 Revision History


注：以前版本的页码可能与当前版本的页码不同

| <b>Changes from Revision A (October 2014) to Revision B (May 2023)</b>                                                            | <b>Page</b> |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------|
| • 更新了整个文档中的表格、图和交叉参考的编号格式.....                                                                                                    | <b>1</b>    |
| • 通篇去除了图像的颜色.....                                                                                                                 | <b>1</b>    |
| • Changed the description of V7V pin in the <i>Pin Functions</i> table.....                                                       | <b>4</b>    |
| • Moved the storage temperature row in the <i>ESD Ratings</i> table to the <i>Absolute Maximum Ratings</i> table.....             | <b>6</b>    |
| • Renamed the <i>ESD Ratings</i> table.....                                                                                       | <b>6</b>    |
| • Changed the recommended value of capacitor from V7V pin to power ground in <i>V7V Low Dropout Regulator and Bootstrap</i> ..... | <b>20</b>   |
| • Changed the recommended value of C8 in the Typical Application Schematic.....                                                   | <b>25</b>   |
| <b>Changes from Revision * (June 2014) to Revision A (October 2014)</b>                                                           | <b>Page</b> |
| • 将器件状态更改为量产数据.....                                                                                                               | <b>1</b>    |

## 5 Device Comparison Table

| PART NUMBER | DESCRIPTION                                                         | COMMENTS                                                                                                                                                                                 |
|-------------|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TPS65261/-1 | 4.5 to 18 V, triple buck with input voltage power failure indicator | Triple buck 3-A/2-A/2-A output current, features an open-drain RESET signal to monitor input power failure, automatic power sequencing                                                   |
| TPS65262    | 4.5 to 18 V, triple buck with dual adjustable LDOs                  | Triple buck 3-A/1-A/1-A output current, automatic power sequencing. Dual LDOs 200 mA/100 mA                                                                                              |
| TPS65263    | 4.5 to 18 V, triple buck with I <sup>2</sup> C interface            | Triple buck 3-A/2-A/2-A output current, I <sup>2</sup> C controlled dynamic voltage scaling (DVS)                                                                                        |
| TPS65287    | 4.5 to 18 V, triple buck with power switch and push button control  | Triple buck 3-A/2-A/2-A output current, up to 2.1-A USB power with overcurrent setting by external resistor, push-button control for intelligent system power-on and power-off operation |
| TPS65288    | 4.5 to 18 V, triple buck with dual power switches                   | Triple buck 3-A/2-A/2-A output current, two USB power switches current limiting at typical 1.2 A (0.8, 1.0, 1.4, 1.6, 1.8, 2.0, and 2.2 A available with manufacture trim options)       |

## 6 Pin Configuration and Functions



(There is no electric signal down bonded to thermal pad inside IC. Exposed thermal pad must be soldered to PCB for optimal thermal performance.)

图 6-1. RHB Package 32 Pins (Top View)

表 6-1. Pin Functions

| PIN   |     | DESCRIPTION                                                                                                                                                             |
|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NAME  | NO. |                                                                                                                                                                         |
| LVIN2 | 1   | Input power supply for LDO2. Connect LVIN2 pin as close as possible to the (+) terminal of an input ceramic capacitor (suggest 1 $\mu$ F).                              |
| LOUT2 | 2   | LDO2 output. Connect LOUT2 pin as close as possible to the (+) terminal of an output ceramic capacitor (suggest 1 $\mu$ F).                                             |
| LFB2  | 3   | Feedback Kelvin sensing pin for LDO2 output voltage. Connect this pin to LDO2 resistor divider.                                                                         |
| LEN2  | 4   | Enable for LDO2. Float to enable.                                                                                                                                       |
| PGOOD | 5   | An open-drain output, asserts low if the output voltage of any buck is beyond regulation range due to thermal shutdown, overcurrent, undervoltage, or ENx shut down.    |
| MODE  | 6   | When high, an automatic power-up or power-down sequence is provided according to the states of EN1, EN2, and EN3 pins.                                                  |
| FB2   | 7   | Feedback Kelvin sensing pin for buck2 output voltage. Connect this pin to buck2 resistor divider.                                                                       |
| EN2   | 8   | Enable for buck2. Float to enable. Can use this pin to adjust the input undervoltage lockout of buck2 with a resistor divider.                                          |
| BST2  | 9   | Boot-strapped supply to the high-side floating gate driver in buck2. Connect a capacitor (recommend 47 nF) from BST2 pin to LX2 pin.                                    |
| LX2   | 10  | Switching node connection to the inductor and bootstrap capacitor for buck2. The voltage swing at this pin is from a diode voltage below the ground up to VIN2 voltage. |

**表 6-1. Pin Functions (continued)**

| PIN   |     | DESCRIPTION                                                                                                                                                                                                  |
|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NAME  | NO. |                                                                                                                                                                                                              |
| PGND2 | 11  | Power ground connection of buck2. Connect PGND2 pin as close as possible to the ( - ) terminal of VIN2 input ceramic capacitor.                                                                              |
| VIN2  | 12  | Input power supply for buck2. Connect VIN2 pin as close as possible to the (+) terminal of an input ceramic capacitor (suggest 10 $\mu$ F).                                                                  |
| VIN3  | 13  | Input power supply for buck3. Connect VIN3 pin as close as possible to the (+) terminal of an input ceramic capacitor (suggest 10 $\mu$ F).                                                                  |
| PGND3 | 14  | Power ground connection of buck3. Connect PGND3 pin as close as possible to the ( - ) terminal of VIN3 input ceramic capacitor.                                                                              |
| LX3   | 15  | Switching node connection to the inductor and bootstrap capacitor for buck3. The voltage swing at this pin is from a diode voltage below the ground up to VIN3 voltage.                                      |
| BST3  | 16  | Boot-strapped supply to the high-side floating gate driver in buck3. Connect a capacitor (recommend 47 nF) from BST3 pin to LX3 pin.                                                                         |
| EN3   | 17  | Enable for buck3. Float to enable. Can use this pin to adjust the input undervoltage lockout of buck3 with a resistor divider.                                                                               |
| FB3   | 18  | Feedback Kelvin sensing pin for buck3 output voltage. Connect this pin to buck3 resistor divider.                                                                                                            |
| AGND  | 19  | Analog ground common to buck controllers and other analog circuits. It must be routed separately from high-current power grounds to the ( - ) terminal of the bypass capacitor of input voltage VIN.         |
| V7V   | 20  | Internal LDO for gate driver and internal controller. Connect a 10- $\mu$ F capacitor from the pin to power ground.                                                                                          |
| COMP1 | 21  | Error amplifier output and loop compensation pin for buck1. Connect a series resistor and capacitor to compensate the control loop of buck1 with peak current PWM mode.                                      |
| SS1   | 22  | Soft-start and tracking input for buck1. An internal 5- $\mu$ A pullup current source is connected to this pin. The soft-start time can be programmed by connecting a capacitor between this pin and ground. |
| FB1   | 23  | Feedback Kelvin sensing pin for buck1 output voltage. Connect this pin to buck1 resistor divider.                                                                                                            |
| EN1   | 24  | Enable for buck1. Float to enable. Can use this pin to adjust the input undervoltage lockout of buck1 with a resistor divider.                                                                               |
| BST1  | 25  | Boot-strapped supply to the high side floating gate driver in buck1. Connect a capacitor (recommend 47 nF) from BST1 pin to LX1 pin.                                                                         |
| LX1   | 26  | Switching node connection to the inductor and bootstrap capacitor for buck1. The voltage swing at this pin is from a diode voltage below the ground up to VIN1 voltage.                                      |
| PGND1 | 27  | Power ground connection of Buck1. Connect PGND1 pin as close as possible to the ( - ) terminal of VIN1 input ceramic capacitor.                                                                              |
| VIN1  | 28  | Input power supply for buck1. Connect VIN1 pin as close as possible to the (+) terminal of an input ceramic capacitor (suggest 10 $\mu$ F).                                                                  |
| LEN1  | 29  | Enable for LDO1. Float to enable.                                                                                                                                                                            |
| LFB1  | 30  | Feedback Kelvin sensing pin for LDO1 output voltage. Connect this pin to LDO1 resistor divider.                                                                                                              |
| LOUT1 | 31  | LDO1 output. Connect LOUT1 pin as close as possible to the (+) terminal of an output ceramic capacitor (suggest 1 $\mu$ F).                                                                                  |
| LVIN1 | 32  | Input power supply for LDO1. Connect LVIN1 pin as close as possible to the (+) terminal of an input ceramic capacitor (suggest 1 $\mu$ F).                                                                   |
| PAD   | —   | There is no electric signal down bonded to thermal pad inside IC. Exposed thermal pad must be soldered to PCB for optimal thermal performance.                                                               |

## 7 Specifications

### 7.1 Absolute Maximum Ratings

over operating free-air temperature (unless otherwise noted) <sup>(1)</sup>

|                  |                                                                | MIN   | MAX | UNIT |
|------------------|----------------------------------------------------------------|-------|-----|------|
| Voltage          | VIN1, VIN2, VIN3                                               | – 0.3 | 20  | V    |
|                  | LX1, LX2, LX3 (maximum withstand voltage transient <20 ns)     | – 1   | 20  |      |
|                  | BST1, BST2, BST3 referenced to LX1, LX2, LX3 pins respectively | – 0.3 | 7   |      |
|                  | MODE, LEN1, LEN2, EN1, EN2, EN3, PGOOD, V7V                    | – 0.3 | 7   |      |
|                  | LOUT1, LOUT2, LVIN1, LVIN2                                     | – 0.3 | 7   |      |
|                  | FB1, FB2, FB3, LFB1, LFB2, COMP1, SS1                          | – 0.3 | 3.6 |      |
|                  | AGND, PGND1, PGND2, PGND3                                      | – 0.3 | 0.3 |      |
| T <sub>J</sub>   | Operating junction temperature                                 | – 40  | 125 | °C   |
| T <sub>stg</sub> | Storage temperature range                                      | –55   | 150 | °C   |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

### 7.2 ESD Ratings

|                                            |                                                                                          | MIN    | MAX  | UNIT |
|--------------------------------------------|------------------------------------------------------------------------------------------|--------|------|------|
| V <sub>(ESD)</sub> Electrostatic discharge | Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>                        | – 2000 | 2000 | V    |
|                                            | Charged device model (CDM), per JEDEC specification JESD22-C101, all pins <sup>(2)</sup> | – 500  | 500  |      |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### 7.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

|                |                                                                | MIN   | MAX | UNIT |
|----------------|----------------------------------------------------------------|-------|-----|------|
| Voltage        | VIN1, VIN2, VIN3                                               | 4.5   | 18  | V    |
|                | LX1, LX2, LX3 (maximum withstand voltage transient <20 ns)     | – 0.8 | 18  |      |
|                | BST1, BST2, BST3 referenced to LX1, LX2, LX3 pins respectively | – 0.1 | 6.8 |      |
|                | MODE, LEN1, LEN2, EN1, EN2, EN3, PGOOD, V7V                    | – 0.1 | 6.3 |      |
|                | FB1, FB2, FB3, LFB1, LFB2, COMP1, SS1                          | – 0.1 | 3   |      |
|                | LOUT1, LOUT2, LVIN1, LVIN2                                     | – 0.1 | 5.5 |      |
| T <sub>A</sub> | Operating ambient temperature                                  | – 40  | 85  | °C   |
| T <sub>J</sub> | Operating junction temperature                                 | – 40  | 125 | °C   |

## 7.4 Thermal Information

| THERMAL METRIC <sup>(1)</sup> |                                              | TPS65262-1    | UNIT |
|-------------------------------|----------------------------------------------|---------------|------|
|                               |                                              | RHB (32 PINS) |      |
| $R_{\theta JA}$               | Junction-to-ambient thermal resistance       | 32.0          | °C/W |
| $R_{\theta JC(top)}$          | Junction-to-case (top) thermal resistance    | 24.2          |      |
| $R_{\theta JB}$               | Junction-to-board thermal resistance         | 6.4           |      |
| $\psi_{JT}$                   | Junction-to-top characterization parameter   | 0.2           |      |
| $\psi_{JB}$                   | Junction-to-board characterization parameter | 6.4           |      |
| $R_{\theta JC(bot)}$          | Junction-to-case (bottom) thermal resistance | 1.3           |      |

(1) For more information about traditional and new thermal metrics, see the *IC Package Thermal Metrics* application report, [SPRA953](#).

## 7.5 Electrical Characteristics

$T_A = 25^\circ\text{C}$ ,  $V_{IN} = 12\text{ V}$ ,  $F_{SW} = 600\text{ kHz}$  (unless otherwise noted)

| PARAMETER                         |                                                                | TEST CONDITIONS                                                                                                      | MIN   | TYP   | MAX   | UNIT          |
|-----------------------------------|----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-------|-------|-------|---------------|
| <b>INPUT SUPPLY VOLTAGE</b>       |                                                                |                                                                                                                      |       |       |       |               |
| VIN                               | Input voltage range                                            |                                                                                                                      | 4.5   |       | 18    | V             |
| UVLO                              | VIN undervoltage lockout                                       | VIN rising                                                                                                           | 4     | 4.25  | 4.5   | V             |
|                                   |                                                                | VIN falling                                                                                                          | 3.5   | 3.75  | 4     | V             |
|                                   |                                                                | Hysteresis                                                                                                           |       | 500   |       | mV            |
| IDDSDN                            | Shutdown supply current                                        | EN1 = EN2 = EN3 = MODE = LEN1 = LEN2 = 0 V                                                                           |       | 12    |       | $\mu\text{A}$ |
| IDDQ_NSW                          | Input quiescent current without buck1, buck2, buck3 switching  | EN1 = EN2 = EN3 = 5 V, FB1 = FB2 = FB3 = 0.8 V, LEN1 = LEN2 = 0                                                      |       | 790   |       | $\mu\text{A}$ |
| IDDQ_NSW1                         |                                                                | EN1 = 5 V, EN2 = EN3 = 0 V, FB1 = 0.8 V, LEN1 = LEN2 = 0                                                             |       | 340   |       | $\mu\text{A}$ |
| IDDQ_NSW2                         |                                                                | EN2 = 5 V, EN1 = EN3 = 0 V, FB2 = 0.8 V, LEN1 = LEN2 = 0                                                             |       | 370   |       | $\mu\text{A}$ |
| IDDQ_NSW3                         |                                                                | EN3 = 5 V, EN1 = EN2 = 0 V, FB3 = 0.8 V, LEN1 = LEN2 = 0                                                             |       | 370   |       | $\mu\text{A}$ |
| IDDQ_LDO1                         | LDO input quiescent current                                    | EN1 = EN2 = EN3 = LEN2 = 0 V, LFB1 = 0.8 V, LEN1 = 5 V                                                               |       | 190   |       | $\mu\text{A}$ |
| IDDQ_LDO2                         |                                                                | EN1 = EN2 = EN3 = LEN1 = 0 V, LFB2 = 0.8 V, LEN2 = 5 V                                                               |       | 190   |       | $\mu\text{A}$ |
| V7V                               | V7V LDO output voltage                                         | V7V load current = 0 A                                                                                               | 6     | 6.3   | 6.6   | V             |
| I_OCP_V7V                         | V7V LDO current limit                                          |                                                                                                                      |       | 175   |       | mA            |
| <b>FEEDBACK VOLTAGE REFERENCE</b> |                                                                |                                                                                                                      |       |       |       |               |
| VFB                               | Feedback voltage                                               | $V_{COMP} = 1.2\text{ V}$ , $T_J = 25^\circ\text{C}$                                                                 | 0.595 | 0.6   | 0.605 | V             |
|                                   |                                                                | $V_{COMP} = 1.2\text{ V}$ , $T_J = -40^\circ\text{C}$ to $125^\circ\text{C}$                                         | 0.594 | 0.6   | 0.606 | V             |
| V_LINEREG_BUCK                    | Line regulation-DC <sup>(1)</sup>                              | $I_{OUT1} = 1.5\text{ A}$ , $I_{OUT2} = 1\text{ A}$ , $I_{OUT3} = 1\text{ A}$ , $5\text{ V} < V_{INx} < 18\text{ V}$ |       | 0.002 |       | %/V           |
| V_LOADREG_BUCK                    | Load regulation-DC <sup>(1)</sup>                              | $V_{IN} = 12\text{ V}$ , $I_{OUTx} = (10 - 100\%) \times I_{OUTx\_max}$                                              |       | 0.02  |       | %/A           |
| <b>BUCK1, BUCK2, BUCK3</b>        |                                                                |                                                                                                                      |       |       |       |               |
| V_ENXH                            | EN1, EN2, EN3 high-level input voltage                         |                                                                                                                      |       | 1.2   | 1.26  | V             |
| V_ENXL                            | EN1, EN2, EN3 low-level input voltage                          |                                                                                                                      | 1.1   | 1.15  |       | V             |
| I_ENX                             | EN1, EN2, EN3 pullup current                                   | ENx = 1 V                                                                                                            |       | 3.6   |       | $\mu\text{A}$ |
|                                   |                                                                | ENx = 1.5 V                                                                                                          |       | 6.6   |       |               |
| I_ENhys                           | Hysteresis current                                             |                                                                                                                      |       | 3     |       | $\mu\text{A}$ |
| I_SS1                             | Buck1 soft-start charging current                              |                                                                                                                      | 4.3   | 5     | 6     | $\mu\text{A}$ |
| T_SS2/3                           | Buck2, buck3 soft-start time                                   |                                                                                                                      |       | 1     |       | ms            |
| T_ON_MIN                          | Minimum on time                                                |                                                                                                                      |       | 80    | 100   | ns            |
| G_m_EA1/2/3                       | Error amplifier trans-conductance                              | $-2\text{ }\mu\text{A} < I_{COMPX} < 2\text{ }\mu\text{A}$                                                           |       | 300   |       | $\mu\text{s}$ |
| G_m_PS1/2/3                       | COMP voltage to inductor current G <sub>m</sub> <sup>(1)</sup> | ILX = 0.5 A                                                                                                          |       | 7.4   |       | A/V           |
| I_LIMIT1                          | Buck1 peak inductor current limit                              |                                                                                                                      | 4.4   | 5.1   | 6.06  | A             |
| I_LIMITSOURCE1                    | Buck1 low-side source current limit                            |                                                                                                                      |       | 4.4   |       | A             |
| I_LIMITS1                         | Buck1 low-side sink current limit                              |                                                                                                                      |       | 1.3   |       | A             |
| I_LIMIT2/3                        | Buck2, buck3 peak inductor current limit                       |                                                                                                                      | 1.8   | 2.4   | 3     | A             |
| I_LIMITSOURCE2/3                  | Buck2, buck3 low-side source current limit                     |                                                                                                                      |       | 1.75  |       | A             |
| I_LIMITS2/3                       | Buck2, buck3 low-side sink current limit                       |                                                                                                                      |       | 1     |       | A             |
| T_Hiccup_wait                     | OC wait time <sup>(1)</sup>                                    |                                                                                                                      |       | 0.5   |       | ms            |
| T_Hiccup_re                       | Hiccup time before restart <sup>(1)</sup>                      |                                                                                                                      |       | 14    |       | ms            |
| Rdson_HS1                         | Buck1 high-side switch resistance                              | VIN1 = 12 V                                                                                                          |       | 100   |       | m $\Omega$    |
| Rdson_LS1                         | Buck1 low-side switch resistance                               | VIN1 = 12 V                                                                                                          |       | 65    |       | m $\Omega$    |
| Rdson_HS2                         | Buck2 high-side switch resistance                              | VIN1 = 12 V                                                                                                          |       | 195   |       | m $\Omega$    |
| Rdson_LS2                         | Buck2 low-side switch resistance                               | VIN1 = 12 V                                                                                                          |       | 145   |       | m $\Omega$    |
| Rdson_HS3                         | Buck3 high-side switch resistance                              | VIN1 = 12 V                                                                                                          |       | 195   |       | m $\Omega$    |

## 7.5 Electrical Characteristics (continued)

$T_A = 25^\circ\text{C}$ ,  $V_{IN} = 12\text{ V}$ ,  $F_{SW} = 600\text{ kHz}$  (unless otherwise noted)

| PARAMETER |                                  | TEST CONDITIONS | MIN | TYP | MAX | UNIT       |
|-----------|----------------------------------|-----------------|-----|-----|-----|------------|
| Rdson_LS3 | Buck3 low-side switch resistance | VIN1 = 12 V     |     | 145 |     | m $\Omega$ |

## 7.5 Electrical Characteristics (continued)

$T_A = 25^\circ\text{C}$ ,  $V_{IN} = 12\text{ V}$ ,  $F_{SW} = 600\text{ kHz}$  (unless otherwise noted)

| PARAMETER                               |                                                                            | TEST CONDITIONS                                                                        | MIN   | TYP   | MAX   | UNIT             |
|-----------------------------------------|----------------------------------------------------------------------------|----------------------------------------------------------------------------------------|-------|-------|-------|------------------|
| <b>POWER GOOD, MODE, POWER SEQUENCE</b> |                                                                            |                                                                                        |       |       |       |                  |
| $V_{th\_PG}$                            | Feedback voltage threshold                                                 | FBx undervoltage falling                                                               |       | 92.5  |       | % $V_{REF}$      |
|                                         |                                                                            | FBx undervoltage rising                                                                |       | 95    |       |                  |
|                                         |                                                                            | FBx overvoltage rising                                                                 |       | 107.5 |       |                  |
|                                         |                                                                            | FBx overvoltage falling                                                                |       | 105   |       |                  |
| $T_{DEGLITCH(PG)\_F}$                   | PGOOD falling edge deglitch time                                           |                                                                                        |       | 0.19  |       | ms               |
| $T_{RDEGLITCH(PG)\_R}$                  | PGOOD rising edge deglitch time                                            |                                                                                        |       | 1     |       | ms               |
| $I_{PG}$                                | PGOOD pin leakage                                                          |                                                                                        |       | 0.05  |       | $\mu\text{A}$    |
| $V_{LOW\_PG}$                           | PGOOD pin low voltage                                                      | $I_{SINK} = 1\text{ mA}$                                                               |       | 0.4   |       | V                |
| $V_{MODEH}$                             | MODE high-level input voltage                                              |                                                                                        |       | 1.2   | 1.26  | V                |
| $V_{MODEL}$                             | MODE low-level input voltage                                               |                                                                                        | 1.1   | 1.15  |       | V                |
| $I_{MODE}$                              | MODE pullup current                                                        | MODE = 1 V                                                                             |       | 3.6   |       | $\mu\text{A}$    |
|                                         |                                                                            | MODE = 1.5 V                                                                           |       | 6.6   |       |                  |
| $T_{psdelay}$                           | Delay time between bucks at automatic power sequencing mode <sup>(1)</sup> | MODE = 1.5 V                                                                           |       | 1.7   |       | ms               |
| <b>LDO1 AND LDO2</b>                    |                                                                            |                                                                                        |       |       |       |                  |
| $V_{LENXH}$                             | LEN1, LEN2 high-level input voltage                                        |                                                                                        |       | 1.2   | 1.26  | V                |
| $V_{LENXL}$                             | LEN1, LEN2 low-level input voltage                                         |                                                                                        | 1.1   | 1.15  |       | V                |
| $I_{LENX}$                              | LEN1, LEN2 pullup current                                                  | LENx = 1 V                                                                             |       | 3.6   |       | $\mu\text{A}$    |
|                                         |                                                                            | LENx = 1.5 V                                                                           |       | 6.6   |       |                  |
| $V_{IN\_LDO1}$                          | LDO input voltage range                                                    |                                                                                        | 1.3   |       | 5.5   | V                |
| $V_{OUT\_LDO1}$                         | LDO output voltage range                                                   | Load current = 350 mA                                                                  | 1     |       |       | V                |
| $V_{LDOFB1}$                            | LDO voltage reference                                                      | Load current = 10 mA                                                                   | 0.594 | 0.6   | 0.606 | V                |
| $I_{max\_LDO1}$                         | LDO current limit                                                          |                                                                                        | 350   | 455   | 540   | mA               |
| $V_{dropout1}$                          | LDO dropout voltage                                                        | $I_{OUT} = 20\text{ mA}$                                                               |       | 12    |       | mV               |
|                                         |                                                                            | $I_{OUT} = 350\text{ mA}$                                                              |       | 400   |       | mV               |
| $V_{LINEREG\_LDO1}$                     | LDO line regulation-DC <sup>(1)</sup>                                      | $V_{OUT} = 1.8\text{ V}$ , $I_{OUT} = 10\text{ mA}$ ,<br>LVIN1 changes from 2 to 5.5 V |       | 0.002 |       | %/V              |
| $V_{LOADREG\_LDO1}$                     | LDO load regulation-DC <sup>(1)</sup>                                      | $I_{OUT} = 1\text{ to }350\text{ mA}$ , LVIN1 = 5 V                                    |       | 0.2   |       | %/A              |
| $PSRR_{LDO1}$                           | Ripple rejection <sup>(1)</sup>                                            | LVIN1 = 5 V, $V_{out} = 1.8\text{ V}$ , $I_{OUT} = 10\text{ mA}$ , $f = 10\text{ kHz}$ |       | 56    |       | dB               |
| $V_{IN\_LDO2}$                          | LDO input voltage range                                                    |                                                                                        | 1.3   |       | 5.5   | V                |
| $V_{OUT\_LDO2}$                         | LDO output voltage range                                                   | Load current = 150 mA                                                                  | 1     |       |       | V                |
| $V_{LDOFB2}$                            | LDO voltage reference                                                      | Load current = 10 mA                                                                   | 0.594 | 0.6   | 0.606 | V                |
| $I_{max\_LDO2}$                         | LDO current limit                                                          |                                                                                        | 170   | 220   | 290   | mA               |
| $V_{dropout2}$                          | LDO dropout voltage <sup>(1)</sup>                                         | $I_{OUT} = 10\text{ mA}$                                                               |       | 12    |       | mV               |
|                                         |                                                                            | $I_{OUT} = 150\text{ mA}$                                                              |       | 250   |       |                  |
| $V_{LINEREG\_LDO2}$                     | LDO line regulation-DC <sup>(1)</sup>                                      | $V_{OUT} = 1.8\text{ V}$ , $I_{OUT} = 10\text{ mA}$ ,<br>LVIN2 changes from 2 to 5.5 V |       | 0.002 |       | %/V              |
| $V_{LOADREG\_LDO2}$                     | LDO load regulation-DC <sup>(1)</sup>                                      | $I_{OUT} = 1\text{ to }150\text{ mA}$ , LVIN2 = 5 V                                    |       | 0.2   |       | %/A              |
| $PSRR_{LDO2}$                           | Ripple rejection <sup>(1)</sup>                                            | LVIN2 = 5 V, $V_{out} = 1.8\text{ V}$ , $I_{OUT} = 10\text{ mA}$ , $f = 10\text{ kHz}$ |       | 56    |       | dB               |
| <b>OSCILLATOR</b>                       |                                                                            |                                                                                        |       |       |       |                  |
| $F_{SW}$                                | Switching frequency                                                        |                                                                                        | 570   | 600   | 630   | kHz              |
| <b>THERMAL PROTECTION</b>               |                                                                            |                                                                                        |       |       |       |                  |
| $T_{TRIP\_OTP}$                         | Thermal protection trip point <sup>(1)</sup>                               | Temperature rising                                                                     |       | 160   |       | $^\circ\text{C}$ |
| $T_{HYST\_OTP}$                         |                                                                            | Hysteresis                                                                             |       | 20    |       | $^\circ\text{C}$ |

(1) Lab validation result

## 7.6 Typical Characteristics

$T_A = 25^\circ\text{C}$ ,  $V_{IN} = 12\text{ V}$ ,  $V_{OUT1} = 1.2\text{ V}$ ,  $V_{OUT2} = 1.8\text{ V}$ ,  $V_{OUT3} = 3.3\text{ V}$   $F_{SW} = 600\text{ kHz}$  (unless otherwise noted)




图 7-1. BUCK1 Efficiency




图 7-2. BUCK2 Efficiency




图 7-3. BUCK1, Load Regulation




图 7-4. BUCK2, Load Regulation




图 7-5. BUCK3, Load Regulation




图 7-6. BUCK1, Line Regulation

## 7.6 Typical Characteristics (continued)

$T_A = 25^\circ\text{C}$ ,  $V_{IN} = 12\text{ V}$ ,  $V_{OUT1} = 1.2\text{ V}$ ,  $V_{OUT2} = 1.8\text{ V}$ ,  $V_{OUT3} = 3.3\text{ V}$ ,  $F_{SW} = 600\text{ kHz}$  (unless otherwise noted)




图 7-7. BUCK2, Line Regulation




图 7-8. BUCK3, Line Regulation




图 7-9. LDO1, Load Regulation




图 7-10. LDO2, Load Regulation




图 7-11. LDO1, Line Regulation




图 7-12. LDO2, Line Regulation

## 7.6 Typical Characteristics (continued)

$T_A = 25^\circ\text{C}$ ,  $V_{IN} = 12\text{ V}$ ,  $V_{OUT1} = 1.2\text{ V}$ ,  $V_{OUT2} = 1.8\text{ V}$ ,  $V_{OUT3} = 3.3\text{ V}$ ,  $F_{SW} = 600\text{ kHz}$  (unless otherwise noted)




图 7-13. Voltage Reference vs Temperature




图 7-14. Oscillator Frequency vs Temperature




图 7-15. Shutdown Quiescent Current vs Temperature




图 7-16. EN Pin Pullup Current vs Temperature, EN = 1 V




图 7-17. EN Pin Pullup Current vs Temperature, EN = 1.5 V




图 7-18. EN Pin Threshold Rising vs Temperature

## 7.6 Typical Characteristics (continued)

$T_A = 25^\circ\text{C}$ ,  $V_{IN} = 12\text{ V}$ ,  $V_{OUT1} = 1.2\text{ V}$ ,  $V_{OUT2} = 1.8\text{ V}$ ,  $V_{OUT3} = 3.3\text{ V}$ ,  $F_{SW} = 600\text{ kHz}$  (unless otherwise noted)




图 7-19. EN Pin Threshold Falling vs Temperature




图 7-20. SS Pin Charge Current vs Temperature




图 7-21. Buck1 High-Side Current Limit vs Temperature




图 7-22. Buck2, 3 High-Side Current Limit vs Temperature




图 7-23. LDO Current Limit vs Temperature




图 7-24. LDO2 Current Limit vs Temperature

## 8 Detailed Description

### 8.1 Overview

The TPS65262-1 is a monolithic, triple-synchronous step-down (buck) converter with 3-A/1-A/1-A output currents. A wide 4.5- to 18-V input supply voltage range encompasses most intermediate bus voltages operating off 5-V, 9-V, 12-V, or 15-V power bus. The feedback voltage reference for each buck is 0.6 V. Each buck is independent with dedicated enable, soft-start, and loop compensation.

The TPS65262-1 implements a constant frequency, peak current mode control that simplifies external loop compensation. The switching frequency is fixed 600 kHz. The switching clock of buck1 is 180° out-of-phase operation from the clocks of buck2 and buck3 channels to reduce input current ripple, input capacitor size, and power-supply-induced noise.

The TPS65262-1 is designed for safe monotonic startup into prebiased loads. The default start up is when VIN is typically 4.25 V. The ENx pin can also be used to adjust the input voltage undervoltage lockout (UVLO) with an external resistor divider. In addition, the ENx pin has an internal 3.6-μA current source, so the EN pin can be floating for automatically powering up the converters.

The TPS65262-1 reduces the external component count by integrating the bootstrap circuit. The bias voltage for the integrated high-side MOSFET is supplied by a capacitor between the BST and LX pins. A UVLO circuit monitors the bootstrap capacitor voltage VBST-VLX in each buck. When VBST-VLX voltage drops to the threshold, LX pin is pulled low to recharge the bootstrap capacitor. The TPS65262-1 can operate at 100% duty cycle as long as the bootstrap capacitor voltage is higher than the BOOT-LX UVLO threshold, which is typically 2.1 V.

The TPS65262-1 features a PGOOD pin to supervise each output voltage of buck converters. The TPS65262-1 has power good comparators with hysteresis, which monitor the output voltages through feedback voltages. When all bucks are in regulation range and power sequence is done, PGOOD is asserted to high.


The SS (soft-start/tracking) pin is used to minimize inrush currents during power-up. A small-value capacitor or resistor divider is coupled to the pin for soft-start or voltage tracking.

At light loading, TPS65262-1 automatically operates in PSM to save power.

The TPS65262-1 integrates low dropout voltage linear regulators (LDO) with input voltage from 1.3 to 5.5 V, independent enable, and adjustable outputs, up to 350 mA for LDO1 and 150 mA for LDO2 continuous output current.

The TPS65262-1 is protected from overload and overtemperature fault conditions. The converter minimizes excessive output overvoltage transients by taking advantage of the power good comparator. When the output is more than 107.5% of the 0.6-V reference voltage, the high-side MOSFET is turned off until the internal feedback voltage is lower than 105% of the 0.6-V reference voltage. The TPS65262-1 implements both high-side MOSFET overload protection and bidirectional low-side MOSFET overload protections to avoid inductor current runaway. If the overcurrent condition lasts for more than the OC wait time (0.5 ms), the converter shuts down and restarts after the hiccup time (14 ms). The TPS65262-1 shuts down if the junction temperature is higher than thermal shutdown trip point 160°C. When the junction temperature drops 20°C (typical) below the thermal shutdown trip point, the TPS65262-1 is restarted under control of the soft-start circuit automatically.

## 8.2 Functional Block Diagram



## 8.3 Feature Description

### 8.3.1 Adjusting the Output Voltage

The output voltage of each buck is set with a resistor divider from the output of buck to the FB pin. TI recommends to use 1% tolerance, or better, divider resistors.




图 8-1. Voltage Divider Circuit

$$R_2 = R_1 \times \frac{0.6}{V_{out} - 0.6} \quad (1)$$

To improve efficiency at light loads, consider using larger value resistors. If the values are too high, the regulator is more sensitive to noise. 表 8-1 shows the recommended resistor values.

**表 8-1. Output Resistor Divider Selection**

| Output Voltage (V) | R1 (kΩ) | R2 (kΩ) |
|--------------------|---------|---------|
| 1                  | 10      | 15      |
| 1.2                | 10      | 10      |
| 1.5                | 15      | 10      |
| 1.8                | 20      | 10      |
| 2.5                | 31.6    | 10      |
| 3.3                | 45.3    | 10      |
| 3.3                | 22.6    | 4.99    |
| 5                  | 73.2    | 10      |
| 5                  | 36.5    | 4.99    |

### 8.3.2 Enable and Adjusting UVLO

The EN1, EN2, and EN3 pins provide electrical on and off control of the device. When the EN1, EN2, and EN3 pins' voltage exceeds the threshold voltage, the device starts operation. If each ENx pin voltage is pulled below the threshold voltage, the regulator stops switching and enters low I<sub>q</sub> state.

The EN pin has an internal pullup current source, allowing the user to float the EN pin for enabling the device. If an application requires controlling the EN pin, use open-drain or open-collector output logic to interface with the pin.

The device implements internal UVLO circuitry on the VIN pin. The device is disabled when the VIN pin voltage falls below the internal VIN UVLO threshold. The internal VIN UVLO threshold has a hysteresis of 500 mV. If an application requires a higher UVLO threshold on the VIN pin, then the ENx pin can be configured as shown in 图 8-2. When using the external UVLO function, TI recommends to set the hysteresis to be greater than 500 mV.

The EN pin has a small pullup current, I<sub>p</sub>, which sets the default state of the pin to enable when no external components are connected. The pullup current is also used to control the voltage hysteresis for the UVLO function because it increases by I<sub>h</sub> after the EN pin crosses the enable threshold. The UVLO thresholds can be calculated using 方程式 2 and 方程式 3.

$$R_1 = \frac{V_{START} \left( \frac{V_{ENFALLING}}{V_{ENRISING}} \right) - V_{STOP}}{I_p \left( 1 - \frac{V_{ENFALLING}}{V_{ENRISING}} \right) + I_h} \quad (2)$$

$$R_2 = \frac{R_1 \times V_{ENFALLING}}{V_{STOP} - V_{ENFALLING} + R_1 (I_h + I_p)} \quad (3)$$

where

- I<sub>h</sub> = 3 μA
- I<sub>p</sub> = 3.6 μA
- V<sub>ENRISING</sub> = 1.2 V
- V<sub>ENFALLING</sub> = 1.15 V




图 8-2. Adjustable VIN UVLO

### 8.3.3 Soft-Start Time

The voltage on the SS1 pin controls the start-up of buck1 output. When the voltage on the SS1 pin is less than the internal 0.6-V reference, The TPS65262-1 regulates the internal feedback voltage to the voltage on the SS1 pin instead of 0.6 V, allowing VOUT to rise smoothly from 0 V to its regulated voltage without inrush current. The device has an internal pullup current source of 5  $\mu\text{A}$  (typical) that charges an external soft-start capacitor to provide a linear ramping voltage at SS1 pin.

Buck1's soft-start time can be calculated approximately by [方程式 4](#).

Buck2 and Buck3 have fixed 1-ms soft-start time.

$$T_{ss}(\text{ms}) = \frac{C_{ss}(\text{nF}) \times V_{ref}(\text{V})}{I_{ss}(\mu\text{A})} \quad (4)$$


### 8.3.4 Power-Up Sequencing

TPS65262-1 features a comprehensive sequencing circuit for the three bucks. If the MODE pin is driving to high at the same time EN1 or EN2 pin (or both), the automatic power-up and power-down sequence function is active. If MODE pin ties low to ground, three buck on or off is separately controlled by three enable pins.

#### 8.3.4.1 External Power Sequencing

The TPS65262-1 has a dedicated enable pin for each converter. The converter enable pins are biased by a current source that allows for easy sequencing with the addition of an external capacitor. Disabling the converter with an active pulldown transistor on the ENx pin allows for a predictable power-down timing operation. [图 8-3](#) shows the timing diagram of a typical buck power-up sequence with a capacitor connected at ENx pin.

A typical 1.4- $\mu\text{A}$  current charges the ENx pin from the input supply when the ENx pin voltage is lower than typical 0.4 V. The internal 7V LDO turns on when the ENx pin voltage rises to typical 0.4 V and a 3.6- $\mu\text{A}$  pullup current sources ENx. After the ENx pin voltage reaches 1.2 V typical, 3- $\mu\text{A}$  hysteresis current sources to the pin to improve noise sensitivity. If all output voltages are in regulation, PGOOD is asserted after PGOOD deglitch time.




**图 8-3. Startup Power Sequence**

### 8.3.4.2 Automatic Power Sequencing

The TPS65262-1 starts with a predefined power-up and power-down sequence when the MODE pin is driven to high. As shown in 表 8-2, the sequence is dictated by different combinations of the EN1 and EN2 status. EN3 is used to start or stop the converters. Buck2 and buck3 are identical converters and can be swapped in the system operation to allow for additional sequencing stages. 图 8-4 shows the power sequencing when EN1 and EN2 are pulled up high.

**表 8-2. Power Sequencing**

|                                  | MODE | EN1                         | EN2                         | EN3                                     | Start Sequencing  | Shutdown Sequencing |
|----------------------------------|------|-----------------------------|-----------------------------|-----------------------------------------|-------------------|---------------------|
| Automatic power sequencing       | High | High                        | High                        | Used to start or stop bucks in sequence | Buck1→buck2→buck3 | Buck3→buck2→buck1   |
|                                  | High | Low                         | High                        |                                         | Buck2→buck1→buck3 | Buck3→buck1→buck2   |
|                                  | High | High                        | Low                         |                                         | Buck2→buck3→buck1 | Buck1→buck3→buck2   |
|                                  | High | Low                         | Low                         | Reserved                                | Reserved          | Reserved            |
| Externally controlled sequencing | Low  | Used to start or stop buck1 | Used to start or stop buck2 | Used to start or stop buck3             | x                 | x                   |



**图 8-4. Automatic Power Sequencing**

### 8.3.5 V7V Low Dropout Regulator and Bootstrap

Power for the high-side and low-side MOSFET drivers and most other internal circuitry is derived from the V7V pin. The internal built-in low dropout linear regulator (LDO) supplies 6.3 V (typical) from VIN to V7V. A 10-μF ceramic capacitor must be connected from V7V pin to power ground.

If the input voltage, VIN decreases to UVLO threshold voltage, the UVLO comparator detects V7V pin voltage and forces the converter off.

Each high-side MOSFET driver is biased from the floating bootstrap capacitor, CB, shown in 图 8-5, which is normally recharged during each cycle through an internal low-side MOSFET or the body diode of low-side MOSFET when the high-side MOSFET turns off. The boot capacitor is charged when the BST pin voltage is less than VIN and the BST-LX voltage is below regulation. The recommended value of this ceramic capacitor is 47 nF. TI recommends a ceramic capacitor with an X7R or X5R grade dielectric with a voltage rating of 10 V or higher because of the stable characteristics over temperature and voltage. Each low-side MOSFET driver is powered from V7V pin directly.

To improve dropout, the device is designed to operate at 100% duty cycle as long as the BST to LX pin voltage is greater than the BST-LX UVLO threshold, which is typically 2.1 V. When the voltage between BST and LX drops below the BST-LX UVLO threshold, the high-side MOSFET is turned off and the low-side MOSFET is turned on allowing the boot capacitor to be recharged.



input or output voltages. Calculate the threshold of peak inductor current to turn off high-side power MOSFET with 方程式 5.

$$I_{L\_PEAK} = 230\text{mA} + \frac{v_{in} - v_{out}}{L} \times t_{dly} \quad (5)$$

After the charge accumulated on the Vout capacitor is more than loading needs, the COMP pin voltage drops to low voltage driven by error amplifier. There is an internal comparator at the COMP pin. If the comp voltage is lower than 0.35 V, the power stage stops switching to save power.




图 8-6. PSM Current Comparator

### 8.3.9 Slope Compensation

To prevent subharmonic oscillations when the device operates at duty cycles greater than 50%, the device adds built-in slope compensation, which is a compensating ramp to the switch current signal.

### 8.3.10 Overcurrent Protection (OCP)

The device is protected from overcurrent conditions by cycle-by-cycle current limiting on both the high-side MOSFET and low-side MOSFET.

#### 8.3.10.1 High-Side MOSFET OCP

The device implements current mode control which uses the COMP pin voltage to control the turn off of the high-side MOSFET and the turn on of the low-side MOSFET on a cycle-by-cycle basis. Each cycle the switch current and the current reference generated by the COMP pin voltage are compared. When the peak switch current intersects the current reference, the high-side switch is turned off.

#### 8.3.10.2 Low-Side MOSFET OCP

While the low-side MOSFET is turned on, its conduction current is monitored by the internal circuitry. During normal operation, the low-side MOSFET sources current to the load. At the end of every clock cycle, the low-side MOSFET sourcing current is compared to the internally set low-side sourcing current limit. If the low-side sourcing current is exceeded, the high-side MOSFET is not turned on and the low-side MOSFET stays on for the next cycle. The high-side MOSFET is turned on again when the low-side current is below the low-side sourcing current limit at the start of a cycle.

The low-side MOSFET can also sink current from the load. If the low-side sinking current limit is exceeded, the low-side MOSFET is turned off immediately for the rest of that clock cycle. In this scenario, both MOSFETs are off until the start of the next cycle.

Furthermore, if an output overload condition (as measured by the COMP pin voltage) lasts for more than the hiccup wait time (which is programmed for 0.5 ms, shown in 图 8-7) the device shuts down itself and restarts after the hiccup time, 14 ms. The hiccup mode helps to reduce the device power dissipation under severe overcurrent condition.




图 8-7. OCP

### 8.3.11 Power Good

The PGOOD pin is an open-drain output. When feedback voltage of each buck is between 95% (rising) and 105% (falling) of the internal voltage reference, the PGOOD pin pulldown is deasserted and the pin floats. TI recommends to use a pullup resistor between the values of 10 to 100 k $\Omega$  to a voltage source that is 6.3 V or less. The PGOOD is in a defined state when the VIN input voltage is greater than 1 V but with reduced current sinking capability. The PGOOD achieves full current sinking capability when the VIN input voltage is above UVLO threshold, which is 4.25 V typically.

The PGOOD pin is pulled low when any feedback voltage of buck is lower than 92.5% (falling) or greater than 107.5% (rising) of the nominal internal reference voltage. Also, the PGOOD is pulled low, if the input voltage is undervoltage locked up, thermal shutdown is asserted, the EN pin is pulled low or the converter is in a soft-start period.

### 8.3.12 Thermal Shutdown

The internal thermal shutdown circuitry forces the device to stop switching if the junction temperature exceeds 160°C typically. The device reinitiates the power-up sequence when the junction temperature drops below 140°C typically.

## 8.4 Device Functional Modes

### 8.4.1 Operation With $V_{IN} < 4.5$ V (Minimum $V_{IN}$ )

The device operates with input voltages above 4.5 V. The maximum UVLO voltage is 4.5 V and operates at input voltages above 4.5 V. The typical UVLO voltage is 4.25 V, and the device can operate at input voltages above that point. The device also can operate at lower input voltages; the minimum UVLO voltage is 4 V (rising) and 3.5 V (falling). At input voltages below the UVLO minimum voltage, the device does not operate.

### 8.4.2 Operation With EN Control

The enable rising edge threshold voltage is 1.2 V typical and 1.26 V maximum. With EN held below that voltage, the device is disabled and switching is inhibited. The IC quiescent current is reduced in this state. When the input voltage is above the UVLO threshold and the EN voltage is increased above the rising edge threshold, the device becomes active. Switching is enabled, and the soft-start sequence is initiated. The device starts at the soft-start time determined by the external soft start capacitor as shown in 图 9-2 to 图 9-7.

### 8.4.3 Operation at Light Loads

The device is designed to operate in high-efficiency PSM under light load conditions. Pulse skipping is initiated when the switch current falls to 0.23 A. During pulse skipping, the low-side FET is turned off. The switching node (LX) waveform takes on the characteristics of DCM operation and the apparent switching frequency decreases as shown in [图 9-8](#), [图 9-10](#), and [图 9-12](#).

## 9 Application and Implementation


### 备注

以下应用部分中的信息不属于 TI 器件规格的范围，TI 不担保其准确性和完整性。TI 的客户应负责确定器件是否适用于其应用。客户应验证并测试其设计，以确保系统功能。

### 9.1 Application Information

The device is triple-synchronous, step-down DC/DC converter with dual LDOs. The device is typically used to convert a higher DC voltage to lower DC voltages with continuous available output current of 3 A/1 A/1 A. The following design procedure can be used to select component values for the TPS65262-1. This section presents a simplified discussion of the design process.

### 9.2 Typical Application



#### 9.2.1 Design Requirements

This example details the design of a triple-synchronous step-down converter. A few parameters must be known to start the design process. These parameters are typically determined at the system level. For this example, start with the following known parameters shown in 表 9-1.

表 9-1. Design Parameters

| PARAMETER                                       | VALUE                    |
|-------------------------------------------------|--------------------------|
| Vout1                                           | 1.2 V                    |
| Iout1                                           | 3 A                      |
| Vout2                                           | 1.8 V                    |
| Iout2                                           | 1 A                      |
| Vout3                                           | 3.3 V                    |
| Iout3                                           | 1 A                      |
| Buck1 transient response 1-A load step          | ±5%                      |
| Buck2, buck3 transient response 0.5-A load step | ±5%                      |
| Input voltage                                   | 12 V normal, 4.5 to 18 V |
| Output voltage ripple                           | ±1%                      |
| Switching frequency                             | 600 kHz                  |

## 9.2.2 Detailed Design Procedure

### 9.2.2.1 Output Inductor Selection

To calculate the value of the output inductor, use 方程式 6. LIR is a coefficient that represents the amount of inductor ripple current relative to the maximum output current. The inductor ripple current is filtered by the output capacitor. Therefore, choosing high inductor ripple currents impact the selection of the output capacitor because the output capacitor must have a ripple current rating equal to or greater than the inductor ripple current. In general, the inductor ripple value is at the discretion of the designer; however, LIR is normally from 0.1 to 0.3 for the majority of applications.

$$L = \frac{V_{inmax} - V_{out}}{I_o \times LIR} \times \frac{V_{out}}{V_{inmax} \times f_{sw}} \quad (6)$$

For the output filter inductor, it is important not to exceed the RMS current and saturation current ratings. The RMS and peak inductor current can be found from 方程式 8 and 方程式 9.

$$I_{ripple} = \frac{V_{inmax} - V_{out}}{L} \times \frac{V_{out}}{V_{inmax} \times f_{sw}} \quad (7)$$

$$I_{Lrms} = \sqrt{I_O^2 + \frac{\left( \frac{V_{out} \times (V_{inmax} - V_{out})}{V_{inmax} \times L \times f_{sw}} \right)^2}{12}} \quad (8)$$

$$I_{Lpeak} = I_{out} + \frac{I_{ripple}}{2} \quad (9)$$

The current flowing through the inductor is the inductor ripple current plus the output current. During power-up, faults, or transient load conditions, the inductor current can increase above the calculated peak inductor current level calculated previously. In transient conditions, the inductor current can increase up to the switch current limit of the device. For this reason, the most conservative approach is to specify an inductor with a saturation current rating equal to or greater than the switch current limit rather than the peak inductor current.

### 9.2.2.2 Output Capacitor Selection

The designer needs to account for three primary considerations when selecting the value of the output capacitor. The output capacitor determines the modulator pole, the output voltage ripple, and how the regulator responds to a large change in load current. The output capacitance must be selected based on the most stringent of these three criteria.

The first criterion is the desired response to a large change in the load current. The output capacitor needs to supply the load with current when the regulator cannot. This situation can occur if there are desired hold-up times for the regulator where the output capacitor must hold the output voltage above a certain level for a specified amount of time after the input power is removed. The regulator is also temporarily not able to supply sufficient output current if there is a large, fast increase in the current needs of the load such as a transition from no load to full load. The regulator usually needs two or more clock cycles for the control loop to see the change in load current and output voltage and adjust the duty cycle to react to the change. The output capacitor must be sized to supply the extra current to the load until the control loop responds to the load change. The output capacitance must be large enough to supply the difference in current for two clock cycles while only allowing a tolerable amount of droop in the output voltage. 方程式 10 shows the minimum output capacitance necessary to accomplish this.

$$C_o = \frac{2 \times \Delta I_{out}}{f_{sw} \times \Delta V_{out}} \quad (10)$$

where

- $\Delta I_{out}$  is the change in output current.
- $f_{sw}$  is the regulator's switching frequency.
- $\Delta V_{out}$  is the allowable change in the output voltage.

方程式 11 calculates the minimum output capacitance needed to meet the output voltage ripple specification.

$$C_o > \frac{1}{8 \times f_{sw}} \times \frac{1}{\frac{V_{ripple}}{I_{ripple}}} \quad (11)$$

where

- $f_{sw}$  is the switching frequency.
- $V_{ripple}$  is the maximum allowable output voltage ripple.
- $I_{ripple}$  is the inductor ripple current.

方程式 12 calculates the maximum ESR an output capacitor can have to meet the output voltage ripple specification.

$$R_{esr} < \frac{V_{ripple}}{I_{ripple}} \quad (12)$$

Additional capacitance deratings for aging, temperature, and DC bias must be factored in, which increase this minimum value. Capacitors generally have limits to the amount of ripple current they can handle without failing or producing excess heat. An output capacitor that can support the inductor ripple current must be specified. Some capacitor data sheets specify the root mean square (RMS) value of the maximum ripple current. 方程式 13 can be used to calculate the RMS ripple current the output capacitor needs to support.

$$I_{corms} = \frac{V_{out} \times (V_{inmax} - V_{out})}{\sqrt{12} \times V_{inmax} \times L \times f_{sw}} \quad (13)$$

### 9.2.2.3 Input Capacitor Selection

The TPS65262-1 requires a high-quality ceramic, type X5R or X7R, input decoupling capacitor of at least 10  $\mu F$  of effective capacitance on the VIN input voltage pins. In some applications, additional bulk capacitance can also be required for the VIN input. The effective capacitance includes any DC bias effects. The voltage rating of the input capacitor must be greater than the maximum input voltage. The capacitor must also have a ripple current

rating greater than the maximum input current ripple of the TPS65262-1. Calculate the input ripple current using 方程式 14.

$$I_{inrms} = I_{out} \times \sqrt{\frac{V_{out}}{V_{inmin}} \times \frac{(V_{inmin} - V_{out})}{V_{inmin}}} \quad (14)$$

The value of a ceramic capacitor varies significantly over temperature and the amount of DC bias applied to the capacitor. The capacitance variations due to temperature can be minimized by selecting a dielectric material that is stable over temperature. X5R and X7R ceramic dielectrics are usually selected for power regulator capacitors because they have a high capacitance to volume ratio and are fairly stable over temperature. The output capacitor must also be selected with the DC bias taken into account. The capacitance value of a capacitor decreases as the DC bias across a capacitor increases. The input capacitance value determines the input ripple voltage of the regulator. Calculate the input voltage ripple using 方程式 15.

$$\Delta V_{in} = \frac{I_{outmax} \times 0.25}{C_{in} \times f_{sw}} \quad (15)$$

#### 9.2.2.4 Loop Compensation

The TPS65262-1 incorporates a peak current mode control scheme. The error amplifier is a transconductance amplifier with a gain of 300  $\mu$ S. A typical type II compensation circuit adequately delivers a phase margin between 60° and 90°.  $C_b$  adds a high frequency pole to attenuate high-frequency noise when needed. To calculate the external compensation components, follow these steps.

1. Switching frequency,  $f_{sw}$ , 600 kHz is appropriate for application depending on L and C sizes, output ripple, EMI, and so forth. It also gives the best trade-off between performance and cost.
2. Set up crossover frequency,  $f_c$ , which is typically between 1/5 and 1/20 of  $f_{sw}$ .
3.  $R_C$  can be determined by 方程式 16.

$$R_C = \frac{2\pi \times f_c \times V_o \times C_o}{G_{m-EA} \times V_{ref} \times G_{m-PS}} \quad (16)$$

where


- $G_{m-EA}$  is the error amplifier gain (300  $\mu$ S)
- $G_{m-PS}$  is the power stage voltage to current conversion gain (7.4 A/V)

4. Calculate  $C_C$  by placing a compensation zero at or before the dominant pole  $\left( f_p = \frac{1}{C_o \times R_L \times 2\pi} \right)$ .

$$C_C = \frac{R_L \times C_o}{R_C} \quad (17)$$

5. Optional  $C_b$  can be used to cancel the zero from the ESR associated with  $C_o$ .

$$C_b = \frac{R_{ESR} \times C_o}{R_C} \quad (18)$$



**图 9-1. DC/DC Loop Compensation**

## 9.2.3 Application Curves




图 9-2. BUCK1, Soft-Start With No Load




图 9-3. BUCK1, Soft-Start With Full Load




图 9-4. BUCK2, Soft-Start With No Load




图 9-5. BUCK2, Soft-Start With Full Load




图 9-6. BUCK3, Soft-Start With No Load




图 9-7. BUCK3, Soft-Start With Full Load




图 9-8. Buck1, Steady State Operation at Light Load




图 9-9. Buck1, Steady State Operation at Full Load




图 9-10. Buck2, Steady State Operation at Light Load




图 9-11. Buck2, Steady State Operation at Full Load




图 9-12. Buck3, Steady State Operation at Light Load




图 9-13. Buck3, Steady State Operation at Full Load




图 9-14. Buck1, Load Transient, 0.75 to 1.5 A SR = 0.25 A/µs




图 9-15. Buck1, Load Transient, 1.5 to 2.25 A SR = 0.25 A/µs




图 9-16. Buck2, Load Transient, 0.25 to 0.5 A SR = 0.25 A/µs




图 9-17. Buck2, Load Transient, 0.5 to 0.75 A SR = 0.25 A/µs




图 9-18. Buck3, Load Transient, 0.25 to 0.5 A SR = 0.25 A/µs




图 9-19. Buck3, Load Transient, 0.5 to 0.75 A SR = 0.25 A/µs




图 9-20. Buck1, OCP




图 9-21. Buck1, Hiccup and Recovery




图 9-22. Buck2, OCP




图 9-23. Buck2, Hiccup and Recovery




图 9-24. Buck3, OCP




图 9-25. Buck3, Hiccup and Recovery




图 9-26. Automatic Power Sequencing, MODE = EN1 = EN2 = HIGH




图 9-27. Automatic Power Sequencing, MODE = EN1 = EN2 = HIGH




图 9-28. Automatic Power Sequencing, MODE = EN1 = HIGH, EN2 = LOW




图 9-29. Automatic Power Sequencing, MODE = EN1 = HIGH, EN2 = LOW




图 9-30. Automatic Power Sequencing, MODE = EN2 = HIGH, EN1 = LOW






图 9-31. Automatic Power Sequencing, MODE = EN2 = HIGH, EN1 = LOW



Operating at VIN = 12 V, VOUT1 = 1.2 V / 1.5 A, VOUT2 = 1.8 V / 0.5 A, VOUT3 = 3.3 V / 0.5 A,  
EVM Condition 4 Layers, 64 mm × 69 mm T<sub>A</sub> = 30.5°C

图 9-32. Thermal Signature of TPS65262-1EVM



Operating at VIN = 12 V, VOUT1 = 1.2 V / 3 A, VOUT2 = 1.8 V / 1 A, VOUT3 = 3.3 V / 1 A,  
EVM Condition 4 Layers, 64 mm × 69 mm T<sub>A</sub> = 30.5°C

图 9-33. Thermal Signature of TPS65262-1EVM

## 9.3 Power Supply Recommendations

The devices are designed to operate from an input voltage supply range between 4.5 to 18 V. This input power supply must be well regulated. If the input supply is located more than a few inches from the TPS65262-1 converter, additional bulk capacitance can be required in addition to the ceramic bypass capacitors. An electrolytic capacitor with a value of 47  $\mu$ F is a typical choice.

## 9.4 Layout

### 9.4.1 Layout Guidelines

The TPS65262-1 supports a 2-layer PCB layout, shown in 图 9-34.


Layout is a critical portion of good power supply design. See 图 9-34 for a PCB layout example. The top contains the main power traces for VIN, VOUT, and LX. The top layer also has connections for the remaining pins of the TPS65262-1 and a large top-side area filled with ground. The top-layer ground area must be connected to the bottom-layer ground using vias at the input bypass capacitor, the output filter capacitor, and directly under the TPS65262-1 device to provide a thermal path from the exposed thermal pad land to ground. The bottom layer acts as a ground plane connecting analog ground and power ground.

For operation at full-rated load, the top-side ground area and bottom-side ground plane must provide adequate heat dissipating area. Several signals paths conduct fast changing currents or voltages that can interact with stray inductance or parasitic capacitance to generate noise or degrade the power supply's performance. To help eliminate these problems, the VIN pin must be bypassed to ground with a low-ESR ceramic bypass capacitor with X5R or X7R dielectric. Take care to minimize the loop area formed by the bypass capacitor connections, VIN pins, and ground connections. The VIN pin must also be bypassed to ground using a low-ESR ceramic capacitor with X5R or X7R dielectric.

Because the LX connection is the switching node, the output inductor must be located close to the LX pins, and the area of the PCB conductor minimized to prevent excessive capacitive coupling. The output filter capacitor ground must use the same power ground trace as the VIN input bypass capacitor. Try to minimize this conductor length while maintaining adequate width. The small signal components must be grounded to the analog ground path.

The FB and COMP pins are sensitive to noise so the resistors and capacitors must be located as close as possible to the IC and routed with minimal lengths of trace. The additional external components can be placed approximately as shown in 图 9-34.

### 9.4.2 Layout Example



- 0.010-inch diameter Thermal VIA to Ground Plane
- VIA to Ground Plane

图 9-34. PCB Layout

## 10 Device and Documentation Support

### 10.1 接收文档更新通知

要接收文档更新通知，请导航至 [ti.com](http://ti.com) 上的器件产品文件夹。点击 [订阅更新](#) 进行注册，即可每周接收产品信息更改摘要。有关更改的详细信息，请查看任何已修订文档中包含的修订历史记录。

### 10.2 支持资源

[TI E2E™ 支持论坛](#) 是工程师的重要参考资料，可直接从专家获得快速、经过验证的解答和设计帮助。搜索现有解答或提出自己的问题可获得所需的快速设计帮助。

链接的内容由各个贡献者“按原样”提供。这些内容并不构成 TI 技术规范，并且不一定反映 TI 的观点；请参阅 TI 的《[使用条款](#)》。

### 10.3 Trademarks

TI E2E™ is a trademark of Texas Instruments.  
所有商标均为其各自所有者的财产。

### 10.4 静电放电警告



静电放电 (ESD) 会损坏这个集成电路。德州仪器 (TI) 建议通过适当的预防措施处理所有集成电路。如果不遵守正确的处理和安装程序，可能会损坏集成电路。

ESD 的损坏小至导致微小的性能降级，大至整个器件故障。精密的集成电路可能更容易受到损坏，这是因为非常细微的参数更改都可能会导致器件与其发布的规格不相符。

### 10.5 术语表

[TI 术语表](#)      本术语表列出并解释了术语、首字母缩略词和定义。

## 11 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

## PACKAGING INFORMATION

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| TPS65262-1RHBR   | ACTIVE        | VQFN         | RHB                | 32   | 3000           | RoHS & Green    | NIPDAU                               | Level-2-260C-1 YEAR  | -40 to 85    | TPS<br>65262-1          | <a href="#">Samples</a> |
| TPS65262-1RHBT   | ACTIVE        | VQFN         | RHB                | 32   | 250            | RoHS & Green    | NIPDAU                               | Level-2-260C-1 YEAR  | -40 to 85    | TPS<br>65262-1          | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.


(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.




## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TPS65262-1RHBR | VQFN         | RHB             | 32   | 3000 | 330.0              | 12.4               | 5.3     | 5.3     | 1.1     | 8.0     | 12.0   | Q2            |
| TPS65262-1RHBT | VQFN         | RHB             | 32   | 250  | 180.0              | 12.4               | 5.3     | 5.3     | 1.1     | 8.0     | 12.0   | Q2            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TPS65262-1RHBR | VQFN         | RHB             | 32   | 3000 | 346.0       | 346.0      | 33.0        |
| TPS65262-1RHBT | VQFN         | RHB             | 32   | 250  | 210.0       | 185.0      | 35.0        |


## GENERIC PACKAGE VIEW

**RHB 32**

**VQFN - 1 mm max height**

5 x 5, 0.5 mm pitch

PLASTIC QUAD FLATPACK - NO LEAD



Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.


4224745/A

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The package thermal pad must be soldered to the printed circuit board for thermal and mechanical performance.



**RHB0032E**

**VQFN - 1 mm max height**

PLASTIC QUAD FLATPACK - NO LEAD



LAND PATTERN EXAMPLE  
SCALE:18X



## SOLDER MASK DETAILS

4223442/B 08/2019


NOTES: (continued)

4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 ([www.ti.com/lit/sluea271](http://www.ti.com/lit/sluea271)).
5. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.

**RHB0032E**

**VQFN - 1 mm max height**

PLASTIC QUAD FLATPACK - NO LEAD



## SOLDER PASTE EXAMPLE BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD 33:  
75% PRINTED SOLDER COVERAGE BY AREA UNDER PACKAGE  
SCALE:20X

4223442/B 08/2019

NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

## 重要声明和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做任何明示或暗示的担保，包括但不限于对适销性、某特定用途方面的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他功能安全、信息安全、监管或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的应用。严禁对这些资源进行其他复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。您应全额赔偿因在这些资源的使用中对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，TI 对此概不负责。

TI 提供的产品受 [TI 的销售条款](#) 或 [ti.com](#) 上其他适用条款/TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

邮寄地址：Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2024，德州仪器 (TI) 公司