



Cable Tie, Natural, PA6.6, 8"L (203 mm), 18lb, PK1000

PLT2M-M

The PLT2M-M cable tie provides dependable bundling for indoor installations and general-purpose routing. Miniature cross section, 8.0 in (203mm) long with 18 lb (80 N) minimum loop tensile strength and a 0.06–2 in (1.5–50.8mm) bundle diameter range. It is natural Nylon 6.6 for consistent routing and organization. Operating range -76 to 185°F (-60 to 85°C). Use with GTS-E, GS2B-E, PTS, PPTS, and STS2 tools. Std. pkg. qty. 1000.

Specifications

Product Type	Premium Cable Tie
Color	Natural
Environment	Indoor
Material	Nylon 6.6
Air Handling Space	AH-2 Plenum
Flammability Rating	UL 94 V-2
Overall Length (In.)	8
Overall Length (mm)	203
Body Width (In.)	0.098
Body Width (mm)	2.5
Body Thickness (In.)	0.043
Body Thickness (mm)	1.1
Maximum Bundle Diameter (In.)	2
Maximum Bundle Diameter (mm)	51
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	80
Minimum Loop Tensile Strength (lb)	18
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Compliant
For Use With	GTS-E, GS2B-E, PTS, PPTS, STS2

Specifications (continued)

Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
---------------	--

Packaging Detail

UPC	07498354026
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.0887
Std. Ctn. Qty.	25000
Std. Ctn. Volume (cf)	2.2183