



.025 (.64) PIN - SWAGE MOUNT




GOLD	TIN	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	
1370-2	1371-2	.052 (1.32)

.030 (.76) PIN - SWAGE MOUNT




GOLD	TIN	L	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	Length	
1374-1	1375-1	.051 (1.3)	.067 (1.70)
1374-2	1375-2	.082 (2.1)	
1374-3	1375-3	.113 (2.9)	

.031 (.79) PIN - SOLDER MOUNT




GOLD	TIN	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	
1352-1	1353-1	.043 (1.09)

.032 (.81) PIN - SWAGE MOUNT




GOLD	TIN	L	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	Length	
1354-1	1355-1	.051 (1.3)	.052
1354-2	1355-2	.082 (2.1)	(1.32)

.035 (.90) PIN - SWAGE MOUNT




GOLD	TIN	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	
1380-1	1381-1	.062 (1.57)

.040 (1.0) PIN - SWAGE MOUNT




GOLD	TIN	L	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	Length	
1356-1	1357-1	.051 (1.3)	.076 (1.93)
1356-2	1357-2	.082 (2.1)	
1356-3	1357-3	.113 (2.9)	

.040 (1.0) PIN - SWAGE MOUNT




GOLD	TIN	L	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	Length	
1358-1	1359-1	.051 (1.3)	.043 (1.09)
1358-2	1359-2	.082 (2.1)	

.040 (1.0) PIN - SWAGE MOUNT




GOLD	TIN	L	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	Length	
1405-1	1425-1	.051 (1.3)	.043 (1.09)
1405-2	1425-2	.082 (2.1)	
1405-3	1425-3	.113 (2.9)	

.040 (1.0) PIN - SWAGE MOUNT



GOLD	TIN	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	
1402-3	1422-3	.062 (1.57)

.040 (1.0) KAY PIN - PRESS-FIT




MATERIAL:

Solid Nickel Silver

CAT. NO. 1218


Mtg. Hole
.043 (1.09) Dia.

.050 (1.3) PIN - SWAGE MOUNT




GOLD	TIN	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	
1360-2	1361-2	.064 (1.63)

.063 (1.6) PIN - SWAGE MOUNT




GOLD	TIN	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	
1362-2	1363-2	.067 (1.70)

.080 (2.0) PIN - SWAGE MOUNT




GOLD	TIN	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	
1376-2	1377-2	.094 (2.38)

.080 (2.0) PIN - SWAGE MOUNT




GOLD	TIN	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	
1364-2	1365-2	.094 (2.38)

.080 (2.0) PIN - SWAGE MOUNT




GOLD	TIN	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	
1447-1	1455-1	.094 (2.38)

.080 (2.0) PIN - SWAGE MOUNT



GOLD	TIN	L	Mtg. Hole Dia.
CAT. NO.	CAT. NO.	Length	
1447-2	1455-2	.094 (2.4)	
1447-3	1455-3	.125 (3.2)	.094 (2.38)
1447-4	1455-4	.156 (4.0)	

INSULATED SHORTING PIN



BLUE	RED	BLACK	A	W
CAT. NO.	CAT. NO.	CAT. NO.	Dim.	Dim.
1460L	1460R	1460B	.200 (5.1)	.375 (9.5)
1461L	1461R	1461B	.250 (6.4)	.375 (9.5)
1462L	1462R	1462B	.400 (10.2)	.620 (15.7)
1463L	1463R	1463B	.500 (12.7)	.620 (15.7)

MATERIAL:

Insulator: Polypropylene

Blue, Red or Black


Pin: Brass, Gold Plate

.040 (1.0) PINS



Non-insulated	A
CAT. NO.	Dim.
1430-1	.200 (5.1)
1430-2	.250 (6.4)
1430-3	.300 (7.6)
1430-4	.400 (10.2)
1430-5	.500 (12.7)

SHORTING PIN





MATERIAL:

Pin: Brass,

Gold Plate

INSULATED SHORTING JACK



• For .040 (1.0) Pins

BLUE	RED	BLACK	A	W
CAT. NO.	CAT. NO.	CAT. NO.	Dim.	Dim.
1487L	1487R	1487B	.200 (5.1)	.375 (9.5)
1488L	1488R	1488B	.250 (6.4)	.375 (9.5)
1489L	1489R	1489B	.400 (10.2)	.620 (15.7)

MATERIAL:

Insulator:

Polypropylene

Blue, Red or Black

Spring: Beryllium

Copper, Gold Plate